

## **FIRST TEAM SPORTS, INC**

### **FT187D Super-Duty Double Rim Flex Goal - Product Specification**

1. **GOAL DESIGN** - Rim shall be of a flexible type so as to absorb the shock of player contact. Spring action shall be provided by two heavy-duty wire springs. Netlock system shall be of a continuous type constructed of 3/16"x 1" steel with punched net attachment slots suitable for nylon or chain nets. The rim shall be of an institutional quality with all structural components being no less than 3/16" thick. The assembly shall consist of two official sized 5/8" high strength steel rings and be supported by a 3/16" x 1 1/2" rim support that is welded around 60% of the bottom ring. A single pivot pin must be a minimum 1/2" diameter CF1045 and be welded at final assembly to avoid unsafe accidental disassembly. Rims with non-welded threaded pivot devices are not an acceptable equal. A steel coverplate must enclose all internal mechanisms. Rim shall be punched to attach on any standard front mount backboard, have an orange powdercoat finish and include a heavy-duty nylon net. Mounting hardware shall also be included. Rim shall be made in the USA, carry a 3-Year Superior Warranty and weigh approximately 29#.

**FIRST TEAM SPORTS, INC.  
902 COREY ROAD  
HUTCHINSON, KS 67501  
TOLL FREE: 888-884-6677**