FIRST TEAM SPORTS, INC

Golden Goal Mini - SP Semi-Permanent Soccer Goal (9' x 4.5')

Face of goal shall be constructed of 4" square extruded 6063-T6 aluminum with minimum 3/4" corner radii for player safety and a minimum wall thickness of .080". Net attachment shall be First Team's exclusive "Stay-Put" integrated net attachment design. Other systems using plastic clips, metal clips, velcro, or nylon ties shall not be considered equal.

Rear European style backstays shall be included standard and constructed of 2" square zinc flow coated steel tubing and provide for a 2' top depth. Uprights shall be factory prepped with threaded attachment holes for European backstay assembly.

Design shall allow for 11" of upright to be inserted into FT5001 Ground Sockets.

Units shall include (2) FT5001 Ground Sockets per goal. Ground socket shall be constructed of powder coated steel with chrome plated hinged lid. Sockets shall allow for goal removal when necessary and shall be mower safe when lid is closed.

Crossbar shall attach to uprights by means of 1/2" grade 5 bolts that do not protrude from the front face of the goal.

Goal shall include a minimum 3 mm heavy duty HTPP (High Tenacity Polypropylene) hexagonal mesh net standard.

Entire goal structure, including backstays shall be coated with a white polyester powder coat finish. Goal shall carry a Lifetime Limited Warranty.

Standard features shall include: 3 mm hexagonal mesh net, European style backstays, net stakes, Stay-Put net attachment, ground sockets, padding compensation feature.

System shall weigh approximately 260 lbs./pair

FIRST TEAM SPORTS, INC.
902 COREY ROAD
HUTCHINSON, KS 67501
TOLL FREE: 888-884-6677