

First Team, Inc.
Product Specifications

1/07

Golden Goal 44 Elite-PB Portable Soccer Goal (24'x8')

Face of goal shall be constructed of 4" square extruded 6063-T6 aluminum with minimum $\frac{3}{4}$ " corner radii for player safety and a minimum wall thickness of .080". Net attachment shall be First Team's exclusive "Stay-Put" integrated net attachment design. Other systems using plastic clips, metal clips, velcro, or nylon ties shall not be considered equal.

The upper and rear backstays shall be constructed of 2" square zinc flow coated steel tubing and provide for a 4' top depth and a 10' bottom depth. The lower backstay member shall also employ First Team's exclusive "Stay-Put" net attachment design. A 2" square zinc flow coated ground stabilizer tube shall connect to the rear of the backstays to provide stability during use and transport.

A standard 10" diameter x 2" wide transport wheel shall attach to the front of each side of the goal to facilitate transport. Wheel assembly shall fold toward the rear of the goal without tools during play for safety and be removable if desired.

Goal shall include a minimum 3 mm heavy duty HTPP (High Tenacity Polypropylene) hexagonal mesh net standard.

Entire goal structure, including backstays and ground stabilizer bar shall be coated with a white polyester powder coat finish. Goal shall meet all NCAA, NF, and FIFA rules and comply with ASTM F2025 and shall carry a Lifetime Superior Warranty.

Standard features shall include folding transport wheels, auger type rear hold downs, Stay-Put net attachment, rear stabilizer bar, padding compensation feature.

System shall weigh approximately 500 lbs./pair