

## **FIRST TEAM SPORTS, INC**

### **Golden Goal 44 Jr.Club-SP Semi-Permanent Soccer Goal (18.5'x6.5')**

Face of goal shall be constructed of 4" square extruded 6063-T6 aluminum with minimum 3/4" corner radius for safety and a minimum wall thickness of .080". Net attachment shall be First Team's exclusive "Stay-Put" net attachment design. Other systems using plastic clips, metal clips, velcro, or nylon ties shall not be considered equal.

Rear European style backstays shall be included standard and constructed of 2" square zinc flow coated and provide for a 4' top depth. Uprights shall be factory prepped with threaded attachment holes for Euro backstay assembly.

Design shall allow for 11" of upright to be inserted into FT5001 Ground Sockets.

Units shall include (2) FT5001 Ground Sockets per goal. Ground socket shall be constructed of powder coated with chrome plated hinged lid. Sockets shall allow for goal removal when necessary and shall be closed when is closed.

Crossbar shall attach to uprights by means of 1/2" grade 5 bolts that do not protrude from the front face of goal.

Goal shall include a minimum 3 mm heavy duty HTPP (High Tenacity Polypropylene) hexagonal mesh net.

Entire goal structure, including backstays shall be coated with a white polyester powder coat finish. Goal structure shall carry a Lifetime Superior Warranty.

Standard features shall include: 3 mm hexagonal mesh net, European style backstays, net stakes, Stay-Put attachment, ground sockets, padding compensation feature.

System shall weigh approximately 470 lbs./pair

**FIRST TEAM SPORTS, INC.  
902 COREY ROAD  
HUTCHINSON, KS 67501  
TOLL FREE: 888-884-6677**